


# Optibrush

→ LOGO MAT • OUTDOOR





## → WHY CHOOSE THIS MAT?

Optibrush mats feature your custom logo or artwork on durable nylon monofibers. Combine maximum of 3 colours for the artwork.

- Durable Nylon Brush monofibers made for excellent **scraping action**
- Solution Dyed fibers for **100% UV-resistance**
- **Bleach** and chemical resistant
- Optional **drainage holes** allow for excellent drainage
- 34% postindustrial **recycled content** in the rubber polymer
- Also available as unicolor mat

## → SPECIFICATIONS

<b>SKU</b>	7418, 7446, 7424, 7449
<b>Yarn</b>	100% recycled ECONYL® monofilament nylon yarn <ul style="list-style-type: none"><li>• <b>Yarn weight:</b> 1.300 g/m<sup>2</sup></li><li>• <b>Carpet weight:</b> 1.300 g/m<sup>2</sup></li></ul>
<b>Backing</b>	<ul style="list-style-type: none"><li>• <b>Primary backing:</b> 100% recycled PET non-woven</li><li>• <b>Rubber backing:</b> 100% nitrile rubber with 34% post industrial recycled content in the polymer - phthalate free</li><li>• For maximum oil resistance, durability, and performance. Compression-molded with reinforced borders on all four sides.</li></ul>
<b>Border</b>	<ul style="list-style-type: none"><li>• <b>Border thickness:</b> 2.9 mm</li><li>• <b>Border width:</b> 1.5 cm</li></ul>
<b>Other properties</b>	<ul style="list-style-type: none"><li>• <b>Pile thickness:</b> 10 mm</li><li>• <b>Total weight:</b> 5.20 kg/m<sup>2</sup></li></ul>
<b>Colours</b>	5 Standard colours, Max. 3 colours per design Also available as unicolor mat
<b>Recommended use</b>	Recommended for indoor and outdoor commercial use at entryways, in lobbies, at front desks or anywhere you want to display your company logo, slogan, artwork, or message to customers/visitors or employees. Excellent for scraping action.



## → STANDARD SIZES

60x85	85x150	120x200	150x250
75x85	85x300	120x240	150x300
80x120	120x180	150x200	

## → SPECIAL SIZES




### Max. width

with border: 200 cm  
without border: 195 cm

**Max. length:** 1000 cm

**Size Tolerance:** +/- 2%

## → COLOURS



## → CLEANING INSTRUCTIONS



### **Optibrush mats can be cleaned in several different ways:**

1. They can be commercially laundered (see Laundering Instructions)
2. Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
3. Cleaned with an extractor, or hosed off as necessary to remove heavy soil.

Hang to dry. Mats should always be dry before they are placed back in service.

### **Laundering Instructions**

1. Flush, 2-3 Min. on a medium water level with a maximum temperature of 49°C
2. Flush (optional), 2-3 Min. on a medium water level with a maximum temperature of 49°C
3. Break, 2-3 Min. on a high water level with a maximum temperature of 49 °C
4. Rinse, 2 Min. on a high water level with cold temperature
5. Rinse, 2 Min. on a high water level with cold temperature
6. Extract on low speed, 1-2 Min.
7. Shake out with the drum turning, 1 Min.
8. Extract, on a maximum of 250G, 3-5 Min.
9. Dry (optional), 5-10 Min. with a maximum basket temperature of 82 °C
10. Cool down, 5 Min.

### **Additional recommendations**

- It's recommended that Optibrush mats are washed separate from other mats.
- Optigrafic & Diplomats can be washed together with other SDN mats.
- For Heavy Soiled Mats, increase temperature up to max. 71°C.
- Break should not exceed pH of 9,5; use low pH non-ionic detergents.
- Do not overdry mats; Basket-temperature of dryer should not exceed 82°C.
- If mats are not dried, final rinse can be increased to 49°C. This will reduce moisture retention following extraction.
- Lay Mats flat following removal from washer; allow mats to cool before rolling.